



# ARTISAN SERIES

BY **CAPO FIRESIDE** 

## Fireplace Installation Information

Model (Indoor and Outdoor)	Buckets of Mortar (For Firebox)*	Buckets of Mortar (For Firebrick)	Split Brick	Damper (Indoor only)	Damper Blocks (Indoor Only)**	Flue Size
AS 33"	1	1	56	24" Cast Iron	20"	12"
AS 39"	1	1	85	30" Cast Iron	26"	12"
AS 43" (See-Through)	1	1	42	Exhausto Recommended	N/A	16"
AS 44"	1	1	90	36" Cast Iron	31"	12"
AS 49"	1	1	100	42" Cast Iron	36"	14"
AS 63"	2	1	120	54" Cast Iron	48.5"	16"

\*Each Firebox kit comes with one mortar bucket (63" comes with two buckets)

\*\*When using Cast Iron Damper, Damper Blocks are needed (damper blocks are sold by width of fireplace not damper blocks)

Model (Indoor & Outdoor)	Air Space to Wood Floor (CMU or Metal Base)	Clearance for sides and back of Firebox	Clearance for Masonry Chimneys	Clearance for Metal Chimneys
AS 33"	6"	2"	0"	2"
AS 39"	6"	2"	0"	2"
AS 43" (See-Through)	8"	2"	0"	2"
AS 44"	6"	2"	0"	2"
AS 49"	6"	2"	0"	2"
AS 63"	8"	2"	0"	2"

- All Fireplaces should be inactive for 28 days after installation so that the mortar dries properly. After this, there needs to be 2-3 small test fires before extended use.

### Square Footage for Finishing to Outside of the Unit

Model (Indoor & Outdoor)	Square Footage
AS 39"	52.68 <sup>2</sup> ft.
AS 44"	56.95 <sup>2</sup> ft.
AS 49"	61.22 <sup>2</sup> ft.